



ATIKA®

Dehumidifier **ALE 600 N**

The powerful and reliable dehumidifier
ALE 600 N.

With environmental compatible
refrigerant R290.

For dehumidifying and drying
unfinished buildings and rooms.



Dehumidifier **ALE 600 N**

Can be used universally and efficiently for dehumidifying and drying rooms.

- Robust construction and powerful - optimally suited for construction site use;
- easy to manoeuvre - even on construction sites, because the stable chassis with the handle makes it easy to change location;
- with a roller piston compressor, through which the dehumidifier works efficiently and quietly;
- digital control panel for easy programming and with integrated operating hours counter;
- External water drain that allows continuous operation in high humidity conditions;
- with integrated automatic switch-off, which turns the device off if the water collecting container is full;
- + Hygrostat control that compared the humidity content of the air with the setpoint entered;
- + the built-in automatic defroster allows a dehumidification operation down to a temperature of +5 °C;
- + environmental compatible refrigerant R290R (Propan, GWP 3).



Sturdy chassis with stirrup handle



continuous mode possible



Environmental dehumidifier

To make an active contribution to climate protection, our dehumidifiers are operated with the environmentally friendly refrigerant propane (R290).

Propane R290 is an environmentally friendly and natural refrigerant - an organic compound and belongs to the hydrocarbons and, unlike synthetic refrigerants, has no significant greenhouse effect (GWP=3) or ozone depletion potential (ODP=0).



Dehumidifier

ALE 600 N

Order-no.	303995
AC-motor	230 V~ 50 Hz
Power input P _i	660 W
Working range degree of moisture	30 - 90 %
Working range - temperature	5 - 32 °C
Air output	680 m ³ / h
Dehumidification (30°C / 80% RH)	max. 60 l / 24 h
Room area A _{max} / A _{min}	60-80 m ² / 11 m ²
Room volume (at a ceiling height of 2.5 m)	150 - 200 m ³
Capacity of water collecting container	max. 5.8 l
Refrigerant	R290 (Propan)
Refrigerant - volume	0.230 kg
GWP-Factor (Global warming potential in relation to Co ₂)	3
Protection class	IP X0
Sound pressure level L _{pA}	< 51 dB(A)
Sound power level L _{WA}	< 65 dB(A)
Hygrostat control	✓
Automatic hot gas defrost	✓
Dimensions (length x width x height)	approx. 540 x 465 x 970 mm
Weight	approx. 51.5 kg

Logistic data



580 x 530 x 1035 mm



approx. 55 kg



4 1004265 014785

Technical modifications reserved.



ALTRAD LESCHA ATIKA GMBH
 Josef-Drexler-Str. 8, 89331 Burgau, Germany
 Phone.: +49 (0) 82 22 / 4130-0 - Fax: +49 (0) 82 22 / 4130-24 - E-mail: info@lescha-atika.de
 Internet: www.lescha-atika.de