



CE



# BHB Series

## Hydraulic Breaker BHB 23 & BHB 25

- powerful hydraulic breakers of medium (BHB 23) to heavy (BHB 25) weight, for a wide range of applications.
- vibration-dampened handles, without reduction of the impact force
- equipped as standard with with 1/2" tail-hoses and at-face couplings, suitable for BELLE hydraulic power packs
- designed for various jobs such as breaking of asphalt or concrete



## BHB 23 & BHB 25

- powerful hydraulic breakers of medium (BHB 23) to heavy (BHB 25) weight, for a wide range of applications
- vibration-dampened handles, without reduction of the impact force
- designed for various jobs such as breaking of asphalt or concrete
- equipped as standard with with 1/2" tail-hoses and at-face couplings, suitable for BELLE hydraulic power packs



Smooth-running folding lock for easy and quick change of the chisel.



Vibration-dampened handles, without reduction of the impact force.



Equipped with 1/2" tail-hoses and at-face couplings, suitable for BELLE hydraulic power packs.

Hydraulic Breaker	BHB 23	BHB 25	Logistic Data	
Working pressure	90 - 110 bar	105 - 125 bar	REF	BEBHB23S
Pressure max.	160 bar	160 bar		
Flow	20 l/min	20 l/min		[PU 1] 23.5 kg
Blows per minute	1600	1300		
Breaking force	65 Joule	85 Joule		
Steel size (Chisel)	25 x 108 mm	32 x 160 mm		
Vibration level	11.97 m/s <sup>2</sup>	11.10 m/s <sup>2</sup>	REF	BEBHB25S
Sound power level L <sub>WA</sub>	107 dB(A)	108 dB(A)		
Weight	23.5 kg	28 kg		[PU 1] 28.0 kg
Order-no.	BEBHB23S	BEBHB25S		